



in Serie
en série / in serie

- 13** **ECOCUT - 2406/2406 1½" - ATEX**
2406: Laufrad/Roue/Ruota: Ø 180 mm
Art.-N° 2406-KY-89 2900 min⁻¹, 7.5 kW, 3x400 V
2406: Laufrad/Roue/Ruota: Ø 180 mm
Art.-N° 2406-KY-99 2900 min⁻¹, 7.5 kW, 3x400 V
- 12** **ECOCUT - 2406/2406 1½" - ATEX**
2406: Laufrad/Roue/Ruota: Ø 180 mm
Art.-N° 2406-KY-89 2900 min⁻¹, 7.5 kW, 3x400 V
2406: Laufrad/Roue/Ruota: Ø 163 mm
Art.-N° 2406-KY-98 2900 min⁻¹, 5.5 kW, 3x400 V
- 11** **ECOCUT - 2406/2405 1½" - ATEX**
2406: Laufrad/Roue/Ruota: Ø 180 mm
Art.-N° 2406-KY-89 2900 min⁻¹, 7.5 kW, 3x400 V
2405: Laufrad/Roue/Ruota: Ø 175 mm
Art.-N° 2405-KY-99 2900 min⁻¹, 3.0 kW, 3x400 V
- 10** **ECOCUT - 2406/2405 1½" - ATEX**
2406: Laufrad/Roue/Ruota: Ø 180 mm
Art.-N° 2406-KY-89 2900 min⁻¹, 7.5 kW, 3x400 V
2405: Laufrad/Roue/Ruota: Ø 165 mm
Art.-N° 2405-KY-98 2900 min⁻¹, 2.7 kW, 3x400 V
- 9** **ECOCUT - 2406/2405 1½" - ATEX**
2406: Laufrad/Roue/Ruota: Ø 180 mm
Art.-N° 2406-KY-89 2900 min⁻¹, 7.5 kW, 3x400 V
2405: Laufrad/Roue/Ruota: Ø 150 mm
Art.-N° 2405-KY-97 2900 min⁻¹, 2.2 kW, 3x400 V
- 8** **ECOCUT - 2406/2405 1½" - ATEX**
2406: Laufrad/Roue/Ruota: Ø 163 mm
Art.-N° 2406-KY-88 2900 min⁻¹, 5.5 kW, 3x400 V
2405: Laufrad/Roue/Ruota: Ø 175 mm
Art.-N° 2405-KY-99 2900 min⁻¹, 3.0 kW, 3x400 V
- 7** **ECOCUT - 2406/2405 1½" - ATEX**
2406: Laufrad/Roue/Ruota: Ø 163 mm
Art.-N° 2406-KY-88 2900 min⁻¹, 5.5 kW, 3x400 V
2405: Laufrad/Roue/Ruota: Ø 165 mm
Art.-N° 2405-KY-98 2900 min⁻¹, 2.7 kW, 3x400 V
- 6** **ECOCUT - 2406 1½" - ATEX**
Laufrad/Roue/Ruota: Ø 180 mm
Art.-N° 2406-KY-99 2900 min⁻¹, 7.5 kW, 3x400 V
- 5** **ECOCUT - 2406 1½" - ATEX**
Laufrad/Roue/Ruota: Ø 163 mm
Art.-N° 2406-KY-98 2900 min⁻¹, 5.5 kW, 3x400 V
- 4** **ECOCUT - 2405 1½" - ATEX**
Laufrad/Roue/Ruota: Ø 175 mm
Art.-N° 2405-KY-99 2900 min⁻¹, 3.0 kW, 3x400 V
- 3** **ECOCUT - 2405 1½" - ATEX**
Laufrad/Roue/Ruota: Ø 165 mm
Art.-N° 2405-KY-98 2900 min⁻¹, 2.7 kW, 3x400 V
- 2** **ECOCUT - 2405 1½" - ATEX**
Laufrad/Roue/Ruota: Ø 150 mm
Art.-N° 2405-KY-96 2900 min⁻¹, 2.2 kW, 3x230 V
Art.-N° 2405-KY-97 2900 min⁻¹, 2.2 kW, 3x400 V
- 1** **ECOCUT - 2405 1½" - ATEX**
Laufrad/Roue/Ruota: Ø 133 mm
Art.-N° 2405-KY-94 2900 min⁻¹, 1.5 kW, 3x230 V
Art.-N° 2405-KY-95 2900 min⁻¹, 1.5 kW, 3x400 V



Stufen
Étages / Stadi: 2



Stufen
Étages / Stadi: 1